

Electrical Distribution System



© Confederation of Indian Industry



Transformer

- ❖ **Transformer**
 - ❑ **Heart of Electrical Distribution**
- ❖ **Category**
 - ❑ **Power Transformers**
 - ❑ **Distribution Transformers**

© Confederation of Indian Industry



Loss in Transformer

- ❖ **Efficient Transformer – 1% loss**
 - ❑ **Substantial at higher ratings**
- ❖ **Losses contributed by**
 - ❑ **Core loss – No load loss**
 - ❑ **Copper Loss – Depends on load**

© Confederation of Indian Industry



Transformer Efficiency


- ❖ **Transformer efficiency - 98-99%**
- ❖ **Optimum efficiency occurs at**
 - ❑ **50% load**
 - ❑ **75% load**
 - ❑ **100% load**

© Confederation of Indian Industry



Transformer Efficiency

❖ Optimum efficiency occurs, where



© Confederation of Indian Industry



Three Phase Transformer-Typical Loss Chart

KVA Rating	Iron Loss (Watt)	FL copper Loss (W)
500	1030	6860
750	1420	9500
1000	1770	11820
1250	1820	12000
2000	3000	20000



Types Of Transformers

Distribution Transformer

- ❖ **Normal Efficiency- 98% to 99%**
- ❖ **Iron loss is 10% to 15% of full load copper loss**
- ❖ **Optimum efficiency occurs between 40% to 60% of loading**

© Confederation of Indian Industry



Types Of Transformers


Power Transformer

- ❖ **Normal Efficiency- 99% to 99.5%**
- ❖ **Iron losses is 20% to 25% of full load copper losses**
- ❖ **Optimum efficiency occurs between 60% to 80% of loading**

© Confederation of Indian Industry



Case Study



© Confederation of Indian Industry



Case Study

Background

- ❖ Capacity of transformer 2000 KVA
- ❖ Load on the transformer is 80%
- ❖ Iron loss = 3 kW
- ❖ F L Copper loss = 20 kW

© Confederation of Indian Industry



Operate Both The Transformers In Parallel

Loss calculation

❖ One transformer in operation

$$(3) + 20 \times (0.8)^2 = 15.8 \text{ kW}$$

❖ Both transformers are in operation


$$[(3) + 20 \times (0.4)^2] \times 2 = 12.4 \text{ kW}$$

Annual Savings= Rs 1.1 Lakhs

© Confederation of Indian Industry



Case Study



© Confederation of Indian Industry



Case Study

Background

- ❖ Two Transformers (12.5MVA) are operated parallel
- ❖ Actual total effective load is 6 MVA
- ❖ % load to the individual transformers is 24%
- ❖ Losses
 - ❑ Iron loss = 25 kW
 - ❑ FL. Copper losses = 72 kW

© Confederation of Indian Industry



Isolate One Transformer In Main Substation

Loss calculation

- ❖ Both transformers are in operation

$$[(25) + 72 \times (0.24)^2] \times 2 = 58.2 \text{ kW}$$

- ❖ One transformer operation

$$(25) + 72 \times (0.48)^2 = 41.5 \text{ kW}$$

- ❖ *Isolated one transformer*


$$\text{Savings in kW} = 16.7 \text{ kW}$$

$$\text{Annual savings} = \text{Rs } 5.1 \text{ Lakhs}$$

© Confederation of Indian Industry



Case Study



© Confederation of Indian Industry



Isolate Primary Of The Idle Transformer

❖ Idle transformer consumes power for its inherent magnetization losses

❖ No load loss = 3 kW

Annual Savings = Rs 0.8 Lakhs

© Confederation of Indian Industry



Energy Efficient Amorphous Transformer

- ❖ Recommended to install in the project stage
- ❖ Made up of amorphous metal core
- ❖ 70% reduction in energy loss over iron core transformer



© Confederation of Indian Industry



Comparison of Efficiency

Rating (kVA)	No Load Loss (W)		Efficiency (%)	
	Amorphous	CRGO	Amorphous	CRGO
250	180	570	98.7	98.2
500	250	900	99	98.53
630	200	1000	99.1	98.54
730	365	1250	99.2	98.65
1000	450	1500	99.2	98.68

Cold-Rolled Grain Oriented silicon steel (CRGO).

© Confederation of Indian Industry



Selection Of Transformer

- ❖ **Selection should be based on TOC**
- ❖ **TOC = [Price] + [No load loss x Loss value] + [Load loss x loss value]**

© Confederation of Indian Industry



Power Factor

How Poor operating power factor cost money?

- ❖ **Maximum demand increases for the same load – Increased demand charges**
- ❖ **Draws more current for the same load**
- ❖ **More distribution voltage drop i.e loss in the distribution cable increase**
- ❖ **Copper loss in the transformer increase**

© Confederation of Indian Industry



Improve Overall PF and Reduce MD

❖ Case Study – Cement plant

- Monthly avg PF maintained at 0.96
- Sanctioned MD : 7300 kVA
- Min demand charges : 75% (5475 kVA)

❖ Recorded monthly MD

- 6800 kVA

❖ High demand charges

© Confederation of Indian Industry



Improve Overall PF and Reduce MD

❖ Action taken

- Installed additional capacitor banks & APFC to improve PF

❖ PF improved to 0.995

- kVA demand reduced by 240 kVA

❖ Additional benefits

- Reduced voltage drop in feeders
- Feeder loss reduction
- Cushion for capacity expansion

© Confederation of Indian Industry



Improve Overall PF and Reduce MD

Annual Saving	-	Rs 10.3 Lakhs
Investment	-	Rs 15.0 Lakhs
Payback period	-	18 Months

© Confederation of Indian Industry



Improving PF of Generator

- ❖ **10 MW turbo generator**
 - **Rated PF : 0.8**
 - **Operating PF: 0.9**
- ❖ **Generator delivers active power & reactive power**
- ❖ **Efficiency of TG depends on operating PF**
 - **Higher the PF, higher is the efficiency**

© Confederation of Indian Industry



Improving PF of Generator

- ❖ **Improving PF from 0.9 to 0.96 resulted in improvement in efficiency**
 - **Reduced loss due to reduction in current**
- ❖ **Installed additional capacitor banks and reduced excitation of Gen**

Annual Savings	:	Rs 14.8 Lakhs
Investment	:	Rs 15.0 Lakhs
Payback	:	13 Months

© Confederation of Indian Industry




PF Compensation methods

- ❖ **3 methods**
 - **Centralised compensation**
 - **Distributed compensation**
 - **Mixed compensation**

© Confederation of Indian Industry



Power Factor Compensation Centralized compensation



© Confederation of Indian Industry



Power Factor Compensation

❖ Advantages

- Easy P.F maintenance
- Capacitor maintenance easy

❖ Disadvantages


- More voltage drop in distribution
- Over heating of cable resulting in failure

❖ Suitable if distance between PCC and MCC is less

© Confederation of Indian Industry



Power Factor Compensation Distributed Compensation



Power Factor Compensation

❖ Advantages

- ❑ Minimum voltage drop
- ❑ Low distribution losses


❖ Disadvantages

- ❑ Maintenance is difficult

❖ Applicable where distribution is remote

Power Factor Compensation

Mixed Compensation



© Confederation of Indian Industry



Power Factor Compensation

❖ Advantages

- Good P.F control
- Easy maintenance
- Low distribution losses

❖ Common in Continuous Process industry

© Confederation of Indian Industry



Voltage Drop

- ❖ **Voltage drop is an indication of distribution loss**
- ❖ **Causes of voltage drop**
 - ❑ **Poor power factor**
 - ❑ **Inadequate cable size laid**
 - ❑ **Poor contact surface at**
 - **Cable Termination**
 - **Cable joints**
 - **Contactors/Switches**

© Confederation of Indian Industry



Voltage Drop

- ❖ **In a large complex distribution system, voltage drops are very common**
- ❖ **Acceptable limit in a 3 Ph. System is 4-5 Volts / Phase**
- ❖ **More than 5 V/Phase indicates energy loss in the distribution**

© Confederation of Indian Industry



Voltage Drop Measuring Procedure

- ❖ Measuring instruments should be calibrated
- ❖ Simultaneous measurement of voltage in the feeding and receiving end of the feeder
- ❖ Measure P.F & Current
- ❖ Note down the cable size

© Confederation of Indian Industry



Case Study-Voltage Drops

❖ Voltage drop – PCC to MCC

Measurements

- ❑ Voltage at PCC = 418 V
- ❑ Voltage at MCC = 405 V
- ❑ Drop in Voltage = 13 Volts
- ❑ Load current = 225 A
- ❑ Power factor = 0.6 Lag
- ❑ Cable size = 1R x 3C x 300 Sq.mm

© Confederation of Indian Industry



Case Study-Voltage Drops

- ❖ Cable loss = 5.1 kW
- ❖ Capacitor installed at Load end – 60 kVAr
- ❖ Reduction cable loss = 2.5 kW
- ❖ Capacitor relocated

Annual savings = 0.76 Lakhs

Capacitor Selection

- ❖ Chart Method
- ❖ Formula Method
 - Capacitor required (kVAr)
= kW x {Tan $\cos^{-1}\Phi_1$ – Tan $\cos^{-1}\Phi_2$ }
Cos Φ_1 – Present power factor
- Cos Φ_2 – Desired power factor

Power factor – Individual compensation

❖ Motor end compensation

- ❑ Below 15 HP not economical
- ❑ kVAR of capacitor bank – Appx 25% of motor HP
- ❑ Capacitor current I_c at rated voltage < 90% of no-load current of motor
- ❑ Relay setting should be adjusted after connecting capacitor bank (Current drops after PF improvement)

© Confederation of Indian Industry



Power Factor Compensation

- ❖ Power factor near to 1 is always recommended
- ❖ Avoid leading power factor
- ❖ Same current for 0.8 lag or 0.8 lead

Equipment	Rated kW	Amp	kW	PF
Packer-2 D/C fan	30	58.0	32.0	-0.77
Packer-3 D/C fan	30	52.0	31.5	0.85

© Confederation of Indian Industry



Power Capacitors

- ❖ Capacitor banks install to improve power factor
- ❖ Allowable power loss = 3-5 W/kVAR

Reasons for failure

- ❖ Ageing
- ❖ Input voltage and frequency fluctuation
- ❖ Harmonics present in the system
- ❖ Temperature around the bank
- ❖ Poor quality capacitors use in the construction

© Confederation of Indian Industry



Replace Faulty Capacitor Banks

- ❖ Power measurement taken with digital power meter

Indication:

- ❖ Power consumption above the permissible level
- ❖ Temperature on the body is above ambient temperature

© Confederation of Indian Industry

